

THE BRADLEY GROUP OF COMPANIES' NYLON THREAD LOCKER™ can be applied on both internal and external threads from a patch (90-120°) to a full 360° coverage. This resilient, environmentally safe material is formulated to upgrade any fastener to a re-usable, self-locking fastener that will automatically feed and requires no curing time. The nylon applied 360° will, in addition to locking the fastener, aid in sealing the fastener.

Our nylon is permanently bonded to the fastener threads and compresses upon engagement, causing a counterforce resulting in the torque value required. NYLON THREAD LOCKER™ is available from THE BRADLEY GROUP OF COMPANIES in three colors, white, yellow and black (yellow and black are applied 360° only).

The unique nature of NYLON THREAD LOCKER™ allows us to custom engineer special torque values that conform to our customers' specifications. Normally applied with 1-2 lead and 4-6 threads coated, a custom engineered location and coverage is available.

All colors meet or exceed IFI-124, IFI-524, MIL 18240F and most industry standards. Nylon is resistant to fuels, hydraulic fluids, most commercial solvents, alcohol, gasolines, etc., and has an operating temperature to 250°F (121°C).

THE BRADLEY GROUP OF COMPANIES

PHONE: 1-800-201-7381 * WEB SITE: www.bradleygroupcoatings.com